



## 4.1. Estimation of the concrete's quantity

### Ground floor





### Beams – Slabs

①	S1: $4,40 \times 5,00 \times 0,18$	= 3,96
②	b1,b2: $2 \times [(5,00 - 2 \times 0,40) \times 0,30 \times 0,32]$	= 0,81
③	C1,2,3,4 (part of the joint area): $4 \times (0,40 \times 0,40 \times 0,32)$	= 0,20
	<b>Total</b>	<b>= 4,97 m<sup>3</sup></b>


### Columns

④	C1,2,3,4: $4 \times (0,40 \times 0,40 \times 2,50)$	= 1,60 m <sup>3</sup>
---	---	-----------------------


## 4.2. Estimation of the formworks' quantity

In constructional works, it is common practice to pay the technicians responsible for the formwork implementation, based upon the quantity (in  $m^3$ ) of casted concrete. However, the most proper way is to separate those two things therefore, the following pages regard the estimation of the required moulds.

### Ground floor



Beams – Slabs		$m^2$
S1:	$3,80 \times 5,00 - 4 \times 0,40 \times 0,10 + 2 \times 3,60 \times 0,18$	= 20,136
b1,b2:	$2 \times 5,00 \times 0,50 + 2 \times (5,00 - 2 \times 0,40) \times 0,32 + 2 \times 4,20 \times 0,30$	= 10,208
columns (joints):	$4 \times 0,40 \times 0,50 + 4 \times 0,40 \times 0,32 + 4 \times 0,10 \times 0,32$	= 1,440
		<b>Total = 31,784</b>
Columns:		
	$4 \times (0,40 \times 0,40 \times 2,50)$	= 16,000



**Basement**

Beams – Slabs		<b>m<sup>2</sup></b>
S1:	$4,50 \times 3,90 - 4 \times (0,15 \times 0,15)$	= 17,460
b1,b2:	$2 \times [5,00 \times 0,50 + 4,20 \times 0,32] + 4,20 \times 0,25$	= 9,788
b3:	$4,40 \times 0,50 + 3,60 \times 0,32 + 3,60 \times 0,25$	= 4,252
sw5:	$4,40 \times 0,50 + 3,60 \times 0,32$	= 3,352
internal column sides	$4 \times 2 \times 0,15 \times 0,32$	= 0,384
	<b>Total</b>	= <b>35,236</b>

Columns:	$4 \times (0,40 \times 0,40 \times 2,50) - 2 \times (0,25 \times 2,50)$	= 14,750
Shear wall sw5:	$2 \times (3,60 \times 2,50)$	= 18,000
	<b>Total</b>	= <b>32,750</b>

## 4.4 Estimation of the reinforcements' quantity


### 4.4.1 Ground floor - Slabs

Elem.	Description	Sketch	L (m)	Quant. (v)	Length (L*v)	D. Ø
S1	upper x		4.42	24	105.98	10
	lower x		4.33	25	108.25	10
	lower y		4.93	16	78.88	8
	additional		0.81	15	12.14	8
	additional		0.81	15	12.14	8

### ESTIMATION OF REBARS

Diam. Ø	Mass/m (Kg)	Quantity n	Total length L*n (m)	Additional Mass b (Kg)	Total Mass L*n*sw + b (Kg)
8	0.395	46	103.16	0.0	40.7
10	0.617	49	214.23	0.0	132.1
Sum	-	95	-	0.0	172.8

#### 4.4.2 Ground floor – Beams

Element	Description	Sketch	L (m)	Quant. (v)	Length (L*v)	Diam. Ø
0b1	lower		4.28	1	4.28	14
	lower		5.33	3	16.00	14
	upper		5.37	2	10.75	14
	additional upper		1.75	1	1.75	14
	additional upper		1.75	1	1.75	14
	stirrups		1.61	31	49.85	8
0b2		Same as 0b1				

#### ESTIMATION OF REBARS

Diam. Ø	Mass/m (Kg)	Quantity n	Total length L*n (m)	Additional mass b (Kg)	Total mass L*n*sw + b (Kg)
14	1.210	16	69.07	0.0	83.6
Sum	-	16	-	0.0	83.6

#### ESTIMATION OF STIRRUPS

Diam. Ø	Mass/m (Kg)	Quantity n	Total length L*n (m)	Additional mass b (Kg)	Total mass L*n*sw + b (Kg)
8	0.395	62	99.70	0.0	39.3
Sum	-	62	-	0.0	39.3